

UR90G-SUB ZERO

Caviar Cooler

Product Features

- Internal vertical LED light
- Black interior and exterior
- Great product presentation
- Heated glass door
- Adjustable shelves
- Adjustable feet





Lock

LED light inside door frame

Sub zero table top freezer ideal as caviar cooler

UR90G-SUB ZERO is a tabletop freezer optimized for cooling caviar and other products you may want to keep at sub-zero temperatures.

The sub-zero model has an electronic thermostat and thermometer, which makes sure that the sensitive caviar is not exposed to wrong temperatures.

Ideally caviar should be stored at -6 to 0 degrees Celsius. An ordinary cooler is too warm, and an ordinary freezer is too cold. Storage under wrong temperatures will ruin the quality of the caviar.

A ventilated cooling system makes sure the temperature is even and stable on all shelves.

The thermostat is placed at the back of the unit, so that the temperature is not changed by accident.

Besides functionality and quality, we have also focused on the visual impression. The unit has a sleek design with internal LED lighting in a cold color tone. It has a black interior as well as exterior. It has heated double glass in the door to prevent condensation. The content is presented in the best possible way.

Design and Material		
Door No & Type	1 heated hinged glass door	
Tempered glass	Yes	
Door Reversible	No	
Shelves No & Type	3 wire shelves black	
Shelf Color	Black	
Shelf Dimensions	420 x 300 mm	
Feet / Legs	4 adjustable feet	
Exterior Finish	Black	
Interior Finish	Black	
Interior Light	LED cold white vertically	
Lock	Yes	

Measures and Content			
Temperature Range	°C	-8 to +6	
Climate Class		4	
Gross / Net Weight	kg	39.5 / 35.5	
Gross / Net Volume	I	92 / 81	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R600a	
Refrigerant Charge	g	40	
Thermometer		Yes	

Power and Consumption			
Energy Class		Е	
Energy Consumption	kWh/24h	1.51	
Annual Energy Cons.	kWh/year	551	
Input Power	W	280	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	42	

Dimensions		
Internal Dimension (WxDxH)	mm	439 x 299 x 632
External Dimension (WxDxH)	mm	515 x 542 x 750

Power and Consumption			
Packed Dimension (WxDxH)	mm	570 x 585 x 805	
40ft Container Load	pcs	160	