

## EXTRA1450CD

### Supermarket Multideck Cooler



#### Product Features

- Can be multiplexed - Create uninterrupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- Multiplexing kit as accessory



Glass end walls as standard



60x40 cm boxes fit perfectly

### Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 450mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard.

It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required.

Installation is simple and quick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

| Design and Material |                               |     | Measures and Content  |                    |            | Power and Consumption |          |                           |
|---------------------|-------------------------------|-----|-----------------------|--------------------|------------|-----------------------|----------|---------------------------|
| Door No & Type      | 2 hinged glass doors          |     | Total Display Area    | m <sup>2</sup>     | 2.12       | Energy Class          | D        |                           |
| Tempered glass      | Yes                           |     | Temperature Range     | °C                 | +2 to +6   | Energy Consumption    | kWh/24h  | 12.44                     |
| Door Reversible     | No                            |     | Climate Class         | 3                  |            | Annual Energy Cons.   | kWh/year | 4541                      |
| Shelves No & Type   | 4 black sheet, tilting + base |     | Gross / Net Weight    | kg                 | 400 / 370  | Input Power           | W        | 1200                      |
| Shelf Color         | Black                         |     | Gross / Net Volume    | l                  | 1050 / 900 | Voltage / Frequency   | V/Hz     | 220-240/50                |
| Max load on Shelves | kg/m <sup>2</sup>             | 100 |                       |                    |            | Noise Level           | dB(A)    | 53                        |
| Feet / Legs         |                               |     | Cooling and Functions |                    |            | Dimensions            |          |                           |
| Feet / Legs         | 4 adjustable feet             |     | Type of Controller    | Electronic         |            | Internal Dimension    | mm       | 1450 x 610 x 1399 (WxDxH) |
| Castors             | Option                        |     | Type of Cooling       | Ventilated         |            |                       |          |                           |
| Exterior Finish     | Black / Glass                 |     | Type of Defrost       | Automatic, hot gas |            |                       |          |                           |
| Interior Finish     | Black                         |     | Refrigerant           | R290               |            |                       |          |                           |

**Design and Material**

|                |                    |
|----------------|--------------------|
| Interior Light | 2 x Vertically LED |
| Lock           | No                 |

**Measures and Content**

|                    |   |     |
|--------------------|---|-----|
| Refrigerant Charge | g | 144 |
| Thermometer        |   | Yes |

**Power and Consumption**

|                            |     |                   |
|----------------------------|-----|-------------------|
| External Dimension (WxDxH) | mm  | 1550 x 920 x 2035 |
| Packed Dimension (WxDxH)   | mm  | 1650 x 975 x 2230 |
| 40ft Container Load        | pcs | 14                |