

## **CRNF1224**

## Freezer room

## **Product Features**

- Plug-In ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- · Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Ventilated floor kit as accessory
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access





Strong handle

Shelf as accessory

## Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble.

The cooling unit comes completely pre-mounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door.

The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price.

We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.

Design and Material	
Door No & Type	1 hinged solid door W:580 H:1765
Max Load on Floor kg/m²	2000
Exterior Finish	White
Interior Finish	White
Interior Light	LED
Lock	Yes

Measures and Content		
Internal Volume	m³	4.06
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	450 / 420
Gross / Net Volume	I	

Power and Consumption			
Energy Consumption	kWh/24h	22.49	
Annual Energy Cons.	kWh/year	8208	
Input Power	W	1100	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	60	

Dimensions		
Internal Dimension (WxDxH)	mm	960 x 2160 x 1960

Measures and Conte	ent
Cooling and Functio	ns
Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic, hot gas
Refrigerant	R290
Refrigerant Charge g	150
Thermometer	Yes

Power and Consur	nption	
External Dimension (WxDxH)	mm	1200 x 2400 x 2200
Packed Dimension (WxDxH)	mm	2400 x 1320 x 2400
40ft Container Load	pcs	8
40ft Container Load	pcs	8