


EXTRA1875CD

Supermarket Multideck Cooler

Product Features

- Can be multiplexed Create uninterrupted continuous line
- Temperature Class 3M1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Tilting function for better product display
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Glass end walls as standard
- · Multiplexing kit as accessory







60x40 cm boxes fit perfectly

Full Glass Door Multideck Cooler with Multiplexing Option

EXTRA Multideck is a full glass door quality cooler with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Shelves can be flat or tilted to 10 or 20 degrees with ticket strips and shelf risers as standard.

It is suitable for display of packed fresh meat, dairy or drinks and is ideal for supermarkets, convenience stores, delis and sandwich shops where plug-in refrigeration is required.

Installation is simple and quick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Design and Material		
Door No & Type	3 hinged glass	doors
Tempered glass		Yes
Door Reversible		No
Shelves No & Type	4 black sheet, tilting +	base
Shelf Color		Black
Max load on Shelves	kg/m²	100
Feet / Legs	6 adjustabl	e feet
Castors	C	ption
Exterior Finish	Black /	Glass
Interior Finish		Black

Measures and Content		
Total Display Area	m²	2.72
Temperature Range	°C	+2 to +6
Climate Class		3
Gross / Net Weight	kg	475 / 425
Gross / Net Volume	I	1350 / 1160
Gross / Net Volume	1	1350 / 116

Cooling and Functions	
Type of Controller	Electronic
Type of Cooling	Ventilated
Type of Defrost	Automatic, hot gas
Refrigerant	R290

Power and Consumption			
Energy Class		С	
Energy Consumption	kWh/24h	14.03	
Annual Energy Cons.	kWh/year	5119	
Input Power	W	1300	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	53	

Dimensions		
Internal Dimension (WxDxH)	mm	1875 x 610 x 1399

Design and Material	
Interior Light	2 x Vertically LED
Lock	No

Measures and Co	ntent	
Refrigerant Charge	g	2x144
Thermometer		Yes

Power and Consumption			
External Dimension (WxDxH)	mm	1975 x 920 x 2035	
Packed Dimension (WxDxH)	mm	2075 x 975 x 2230	
40ft Container Load	pcs	12	