

MCX130M

Stainless Steel Multideck

Product Features

- Ideal for impulse sales
- Lockable security shutter
- Ventilated cooling
- Adjustable shelves
- Fully automatic
- · Castors with brake
- LED interior light with switch
- Digital controller and temperature display
- Ticket strip included





lock

Strong castors

Multideck with manual security shutter

The MCX range is an excellent open-front stainless steel multideck designed to enhance your grab-and-go impulse purchases. This versatile unit offers adjustable temperature so it can be suitable for beverages, dairy produce, or packed fresh meat.

The MCX range is a great choice for locations such as cafeterias, hotels, schools, colleges, and university canteens. It caters to the refrigeration needs during service while prioritizing product security during non-service periods.

Safety and security are paramount with the MCX range. Coming with a lockable security shutter, it stops access to the products when food service is not in progress. Additionally, the cabinet comes equipped with lockable castors, expanding its potential locations and maximizing sales opportunities.

Design and Material	
Shelves No & Type	4 adjustable
Shelf Color	Stainless steel
Castors	Castors
Exterior Finish	SS304
Interior Finish	SS304
Interior Light	LED as option

Measures and Content			
Total Display Area	m²	1.46	
Temperature Range	°C	-1 to +5	
Climate Class		3	
Gross / Net Weight	kg	310 / 230	
Gross / Net Volume	I	680 / 580	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R290	
Refrigerant Charge	g	2 x 140	
Thermometer		Yes	

Power and Consumption			
Energy Class		F	
Energy Consumption	kWh/24h	17.67	
Annual Energy Cons.	kWh/year	6449	
Power		1	
Max Ambient		25°C 60% RH	
Input Power	W	1080	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	61	

Dimensions		
Internal Dimension (WxDxH)	mm	1250 x 436 x 1250
External Dimension (WxDxH)	mm	1312 x 740 x 1994
Packed Dimension (WxDxH)	mm	1400 x 790 x 2150
40ft Container Load	pcs	22