

CR 270x270x220

Coldroom Panels 120 mm

Product Features

- Only panels without cooling unit
- Interlocking connection system
- 120 mm panel insulation
- Many customisation possibilities
- Easy access to products
- · Easy assembly
- Anti-slip floor in SS304 stainless steel
- Shelves available as accessory
- Ramp available as accessory for easy access





Strong handle

Lock system

Cold room panels with 120 mm insulation

TEFCOLDs cold room panels are quick to assemble with an easy interlocking system. The interchangeable modular panels allow different positioning of the door, so you can build the room to fit your space.

Cold rooms offer an efficient and affordable solution to chilled bulk storage, and are often used in restaurants, delis, cafes, and in the storage rooms of shops and supermarkets.

Our range of cold room panels are equipped with an effective polyurethane insulation. Combine the panels with one of our energy efficient monoblock refrigeration units for high cooling performance and low energy consumption.

In terms of accessories, you have the option of a ramp to provide easy access with lightweight trolleys and bakery racks (the room is not suitable for pallet jacks/pallet trucks). We also offer shelf rack system kits for optimizing storage space. We also offer cold room panels with a wide door (see WD models). The panels are not suitable for outdoor use.

Design and Material				
Door No & Type	1 hinged solid door			
Max Load on Floor kg/m²	2000			
Exterior Finish	White			
Interior Finish	White			
Lock	Yes			

Measures and Content				
Internal Volume	m³	11.86		
Wall Thickness	mm	120		
Insulation Density	kg/m³	42		
Gross / Net Weight	kg	720 / 700		
Gross / Net Volume	1			

Cooling a	nd Functions	
		4415

Power and Consumption					
		44159			
D: .					
Dimensions					
Internal Dimension (WxDxH)	mm	2460 x 2460 x 1960			
External Dimension (WxDxH)	mm	2700 x 2700 x 2200			
Packed Dimension (WxDxH)	mm	2800 x 1900 x 1600			
40ft Container Load	pcs	4			