



## **MTF210**

Wall Freezer/Cooler

## **Product Features**

- Side-to-center ventilated cooling
- Ideal for optimizing store space
- Easily switchable between cooler and freezer
- Ideal with chest cooler / freezer underneath
- Heated self-closing glass doors
- Automatic defrost
- Telescopic legs



LED light inside door frame



Digital thermostat

## 3-door freezer/cooler wall cabinet for maximizing store space

Save valuable floor space with this brand new MTF model that you can install either as a freezer or cooler; it is perfect for small shops, convenience stores, butchers, supermarkets etc. It has side-to-center ventilation, which makes it possible to stock the cabinet in full depth without affecting the temperature.

Combine the MTF top freezer/cooler with a SFI chest display freezer/cooler underneath to maximize product presentation. It provides a variety of options, as it can be placed against a wall or as an island display. The cabinet comes with a fixed base shelf and two adjustable wire shelves that can be tilted, making it easy to stage products nicely to customers.

Design and Material				
Door No & Type		3 self-closing heated glass doors		
Tempered glass		Yes		
Door Reversible		No		
Shelves No & Type		9 adjustable wire shelves, white		
Shelf Color		White		
Shelf Dimensions		595x423		
Bottom Shelf Dimensions		595 x 375		
Max load on Shelves	kg/m²	196		
Feet / Legs		Strong stand		
Exterior Finish		White		
Interior Finish		White painted steel		
Interior Light		LED		
Lock		No		

Measures and Content				
Total Display Area	m²	1.44		
Temperature Range	°C	-24 to -18 / -1 to +8		
Climate Class		4		
Gross / Net Weight	kg	355 / 288		
Gross / Net Volume	I	893 / 628		

Cooling and Functions				
Type of Controller		Electronic		
Type of Cooling		Ventilated		
Type of Defrost		Automatic		
Refrigerant		R290		
Refrigerant Charge	g	145		
Thermometer		Yes		

Power and Consumption					
Energy Class		D			
Energy Consumption	kWh/24h	16.35			
Annual Energy Cons.	kWh/year	5971			
Input Power	W	1040			
Voltage / Frequency	V/Hz	220-240/50			
Noise Level	dB(A)	58			

	Dimensions				
	Internal Dimension (WxDxH)	mm	1980 x 480 x 947		
	External Dimension (WxDxH)	mm	2100 x 745 x 2430		
	Packed Dimension (WxDxH)	mm	2225 x 790 x 1630		
	40ft Container Load	pcs	15		