

IC501SCE+SO

Scoop Ice Cream Freezer

Product Features

- Sneeze guard in curved glass
- Angled sliding lids with lock
- Great product visibility
- Ideal for branding
- Storage under baskets
- Digital thermometer
- · Castors with brake
- Climate class 5 for high performance in warm surroundings
- Optional Scooping baskets for plastic tubs





Scooping basket option

Scoop wash option

Scoop ice cream freezer - angled and with serveover

The IC-SO range is our price friendly basis chest freezer with a serve over glass top. It is a quality scoop ice cream freezer for a fair price. It is perfect if you wish to add scooping ice cream sales to your business and are on a budget.

This model is the angled version with angled sliding glass lids instead of flat. The lower front of the freezer provides a better display of the content and makes it even more ideal for display of scoop ice cream.

The model is still compact and comes in varies sizes, so that it is perfect for both smaller shops and delis with limited space as well as lager shops, gas stations and supermarkets.

It is on wheels and can easily change location in the shop.

It is ideal for branding for better presentation of the cabinet content.

All the different sizes of this range is optimized for baskets that can hold 5 liter plastic tubs in the top and there is room for storage underneath.

Baskets are optional. Type and number must be ordered under accessories.

Design and Mater	ial
SneezeGuard	Yes
Tempered glass	Yes
Lid No & Type	2 flat angled sliding temp. glass lids
Basket No & Type	Additional (see drawings)
Castors	4 wheels, 2 with brake
Exterior Finish	White
Interior Finish	White painted steel
Lock	Yes

Measures and Content		
Temperature Range	°C	-24 to -14
Climate Class		5
Gross / Net Weight	kg	127 / 117
Gross / Net Volume	I	427 / 398

Cooling and Functions	
Type of Controller	Mechanical
Type of Cooling	Static
Type of Defrost	Manual
Refrigerant	R290

Power and Consumption			
Energy Class		D	
Energy Consumption	kWh/24h	2.55	
Annual Energy Cons.	kWh/year	929	
Input Power	W	191	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	45	

			Dimensions
Internal Dimension mm 1420 x 495 x 710 (WxDxH)	mm 1420 x 495 x 710	ision	

Measures and Co	ntent	
Refrigerant Charge	g	110
Thermometer		Yes

Power and Consumption			
External Dimension (WxDxH)	mm	1550 x 615 x 1295	
Packed Dimension (WxDxH)	mm	1640 x 750 x 1200	
40ft Container Load	pcs	42	