

## IC301SCE+SO

## Scoop Ice Cream Freezer

## **Product Features**

- Sneeze guard in curved glass
- Angled sliding lids with lock
- Storage under baskets
- Castors with brake
- Climate class 5 for high performance in warm surroundings
- Optional Scooping baskets for plastic tubs





Scooping basket option

Scoop wash option

## Scoop ice cream freezer - angled and with serveover

The IC-SO range is our price friendly basis chest freezer with a serve over glass top. It is a quality scoop ice cream freezer for a fair price. It is perfect if you wish to add scooping ice cream sales to your business and are on a budget.

This model is the angled version with angled sliding glass lids instead of flat. The lower front of the freezer provides a better display of the content and makes it even more ideal for display of scoop ice cream.

The model is still compact and comes in varies sizes, so that it is perfect for both smaller shops and delis with limited space as well as lager shops, gas stations and supermarkets.

It is on wheels and can easily change location in the shop.

It is ideal for branding for better presentation of the cabinet content.

All the different sizes of this range is optimized for baskets that can hold 5 liter plastic tubs in the top and there is room for storage underneath.

Baskets are optional. Type and number must be ordered under accessories.

Design and Material		
SneezeGuard	Yes	
Tempered glass	Yes	
Lid No & Type	2 flat angled sliding temp. glass lids	
Basket No & Type	Additional (see drawings)	
Castors	4 wheels, 2 with brake	
Exterior Finish	White	
Interior Finish	White painted steel	
Lock	Yes	

Measures and Content			
Temperature Range	°C	-24 to -14	
Climate Class		5	
Gross / Net Weight	kg	115 / 102	
Gross / Net Volume	I	264 / 230	

Cooling and Functions		
Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	85
Thermometer		Yes

Power and Consumption				
Energy Class		D		
Energy Consumption	kWh/24h	2.08		
Annual Energy Cons.	kWh/year	758		
Input Power	W	141		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	45		

Dimensions		
Internal Dimension (WxDxH)	mm	890 x 495 x 710
External Dimension (WxDxH)	mm	1010 x 615 x 1295

Power and Consun	nption	
Packed Dimension (WxDxH)	mm	1100 x 750 x 1200
40ft Container Load	pcs	64