

## **CRNF2430**

## Freezer room

## **Product Features**

- Plug-In ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access





Strong handle

Shelf as accessory

## Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble.

The cooling unit comes completely pre-mounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door.

The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price.

We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.

Design and Material	
Door No & Type	1 hinged solid door W:700 H:1765
Max Load on Floor kg/m²	2000
Exterior Finish	White
Interior Finish	White
Interior Light	LED
Lock	Yes

Measures and Co	ntent	
Internal Volume	m³	11.68
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	825 / 795
Gross / Net Volume	I	

Cool	ling a	and F	-uncti	ons
------	--------	-------	--------	-----

Power and Consun	nption	
Energy Consumption	kWh/24h	31.78
Annual Energy Cons.	kWh/year	11598
Input Power	W	1630
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions		
Internal Dimension (WxDxH)	mm	2160 x 2760 x 1960

Measures and Co	ntent	
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic, hot gas
Refrigerant		R290
Refrigerant Charge	g	200
Thermometer		Yes

00 x 2200
00 x 2400
4