DB201S

Backbar Cooler

Product Features

- Approx. 56% more energy efficient than previous DB-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves
- LED interior light





Protective thermostat cover

Door holder for loading of the cabinet

Energy-efficient backbar cooler

This new range of DB backbars is highly energy efficient and uses in average 56% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. The temperature is easily adjusted on the electronic thermostat.

The backbar cooler has self-closing sliding doors with double glazed tempered glass, which gives a nice product presentation. The adjustable wire shelves have a white plastic coating for easy maintenance. The backbar is ideal for busy bar environments, and with its black exterior and stucco aluminium interior it has a contemporary look. A great choice for any bar.

The DB range is also available in a variant with hinged doors.

Design and Material				
Door No & Type	2 sliding glass doors			
Door Reversible	No			
Tempered glass	Yes			
Shelves No & Type	4 wire shelves white			
Shelf Color	White			
Shelf Dimensions	395x320 mm			
Max load on kg/m² Shelves	196			
Feet / Legs	4 adjustable feet			
Exterior Finish	Black			
Interior Finish	Stucco aluminium			
Interior Light	LED			
Lock	Yes			

Measures and Content			
Total Display Area	m²	0.47	
Temperature Range	°C	+2 to +10	
Climate Class		4	
Gross / Net Weight	kg	69 / 63	
Gross / Net Volume	ı	190 / 182	

Cooling and Functions			
Type of Controller	Electronic		
Type of Cooling	Ventilated		
Type of Defrost	Automatic		
Refrigerant	R600a		
Refrigerant Charge g	70		
Thermometer	Yes		

Power and Consumption				
Energy Class		Α		
Energy Consumption	kWh/24h	1.14		
Annual Energy Cons.	kWh/year	416		
Power		1		
Max Ambient		30°C at 55% RH		
Input Power	W	115		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	44		

Dimensions		
Internal Dimension (WxDxH)	mm	810 x 418 x 720
External Dimension (WxDxH)	mm	900 x 520 x 870
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96