

CRNF1827

Freezer room

Product Features

- Plug-In ready after assembly
- · Many customisation possibilities
- Easy access to products
- · Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access





Strong handle

Shelf as accessory

Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble.

The cooling unit comes completely pre-mounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door.

The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price.

We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.

Design and Material	
Door No & Type	1 hinged solid door W:700 H:1765
Max Load on Floor kg/m²	2000
Exterior Finish	White
Interior Finish	White
Interior Light	LED
Lock	Yes

Measures and Co	ntent	
Internal Volume	m³	7.52
Wall Thickness	mm	120
Insulation Density	kg/m³	42
Temperature Range	°C	-20 to -10
Climate Class		5
Gross / Net Weight	kg	685 / 655
Gross / Net Volume	I	

Coo	ling	and	Funct	ions
-----	------	-----	-------	------

Power and Consum	nption	
Energy Consumption	kWh/24h	27.02
Annual Energy Cons.	kWh/year	9864
Input Power	W	1510
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	60

Dimensions		
Internal Dimension (WxDxH)	mm	1560 x 2460 x 1960

t
Electronic
Ventilated
Automatic, hot gas
R290
150
Yes

m 1800 x 2700 x 2200
1000 x 2700 x 2200
m 2000 x 1900 x 2400
cs 6