

IC301SCEB

Ice Cream Freezer

Product Features

- Angled display for better presentation
- Curved sliding lids with lock
- Includes full set of baskets
- Ideal for branding
- Digital thermometer
- · Castors with brake
- Climate class 5 for high performance in warm surroundings





Baskets

Chest freezer with curved sliding glass lids

The IC-SCEB freezer is a price friendly compact display chest freezer. It is great for start-up companies, season sale etc. It is very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.

It comes in varies sizes. The many sizes makes the model perfect for smaller shops and delis with limited space as well as larger shops, gas stations, supermarkets etc.

All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

The SCEB-range is with a lower front than back and curved sliding glass lids. Both features provides a better visual display and presentation of the content. This makes the freezer ideal for display of frozen food including ice cream and lollies. Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

Design and Material			
Tempered glass	Yes		
Lid No & Type	2 curved sliding temp. glass lids		
Basket No & Type	4 Wire baskets, white		
Max No. of Baskets pcs	4		
Castors	4 wheels, 2 with brake		
Exterior Finish	White		
Interior Finish	White painted steel		
Interior Light	No		
Lock	Yes		

Measures and Content			
Temperature Range	°C	-24 to -14	
Climate Class		5	
Gross / Net Weight	kg	65 / 57	
Gross / Net Volume	I	264 / 230	

Cooling and Functions			
Type of Controller		Mechanical	
Type of Cooling		Static	
Type of Defrost		Manual	
Refrigerant		R290	
Refrigerant Charge	g	85	
Thermometer		Yes	

Power and Consumption			
Energy Class		D	
Energy Consumption	kWh/24h	2.08	
Annual Energy Cons.	kWh/year	758	
Input Power	W	141	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	45	

Dimensions		
Internal Dimension (WxDxH)	mm	890 x 495 x 710
External Dimension (WxDxH)	mm	1010 x 615 x 949
Packed Dimension (WxDxH)	mm	1100 x 750 x 1010
40ft Container Load	pcs	64