



MTF250B VS

Wall Freezer/Cooler


Product Features

- Easily switchable between cooler and freezer
- Ideal for optimizing store space
- Side-to-center ventilated cooling
- Ideal with chest cooler / freezer underneath
- Energy saving variable speed compressor
- Heated self-closing glass doors
- Black exterior
- Telescopic legs
- Automatic defrost





LED light inside door frame



4-door freezer/cooler wall cabinet for maximizing store space

Save valuable floor space with this brand new MTF model that you can install either as a freezer or cooler; it is perfect for small shops, convenience stores, butchers, supermarkets etc. It has side-to-center ventilation, which makes it possible to stock the cabinet in full depth without affecting the temperature.

Combine the MTF top freezer/cooler with a SFI chest display freezer/cooler underneath to maximize product presentation. It provides a variety of options, as it can be placed against a wall or as an island display. The cabinet comes with a fixed base shelf and two adjustable wire shelves that can be tilted, making it easy to stage products nicely to customers.

Design and Material			
Door No & Type		4 self-closing heated glass doors	
Tempered glass		Yes	
Door Reversible		No	
Shelves No & Type		12 adjustable wire shelves, white	
Shelf Color		White	
Shelf Dimensions		516x423	
Bottom Shelf Dimensions		516 x 375	
Max load on Shelves	kg/m²	196	
Feet / Legs		Strong stand	
Exterior Finish		Black	
Interior Finish		White painted steel	
Interior Light		LED	
Lock		No	

Measures and Content				
Total Display Area	m²	1.73		
Temperature Range	°C	-24 to -18 / -1 to +8		
Climate Class		4		
Gross / Net Weight	kg	400 / 317		
Gross / Net Volume	I	1076 / 650		

Cooling and Func	tions	
Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	145
Thermometer		Yes

Power and Consumption				
Energy Class		C		
Energy Consumption	kWh/24h	9.16		
Annual Energy Cons.	kWh/year	3344		
Power		1		
Max Ambient		30°C 55% RH		
Input Power	W	1072		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	58		

Dimensions		
Internal Dimension (WxDxH)	mm	2380 x 480 x 947
External Dimension (WxDxH)	mm	2500 x 745 x 2430
Packed Dimension (WxDxH)	mm	2625 x 790 x 1630
40ft Container Load	pcs	8