

MTF Mini

Wall Freezer

Product Features

- Ideal for optimizing store space
- Heated self-closing glass doors
- LED illuminated canopy
- Great branding possibilities
- Ideal with chest cooler / freezer underneath
- Adjustable shelves
- Ticket strip and acrylic front riser as standard
- LED interior light with switch
- Requires stand building and cabinet lifting onto stand





Ideal with chest freezer underneath

Digital thermostat

2-door wall top freezer on legs

The compact MTF Mini wall freezer on legs is ideal for optimizing store space and is a great choice for retail stores to keep products at the correct temperature and in sightline of customers. With an LED illuminated canopy, the top case freezer is ideal for applying branding to, creating a stunning display that will be sure to attract the attention of customers.

The wall freezer features static cooling, LED lighting, and heated self-closing glass doors for energy efficiency and visual appeal. The shelves are adjustable and come with ticket strips and acrylic risers. The MTF Mini is designed to be used in combination with our NIC401SCEB chest display freezer. With its small footprint and sleek design, the MTF Mini wall freezer is a space-saving and stylish addition to any retail space.

Design and Material			
Door No & Type	2 hinged self- closing glass doors		
Tempered glass	Yes		
Shelves No & Type	4 adjustable wire shelves, white		
Shelf Dimensions	530x316mm		
Max load on kg/m² Shelves	196		
Canopy Type	Curved		
Canopy Light	LED		
Feet / Legs	Strong stand		
Exterior Finish	White		
Interior Finish	White painted steel		
Interior Light	LED		
Lock	Yes		

Measures and Content			
Total Display Area	m²	0.38	
Temperature Range	°C	-23 to -18	
Climate Class		4	
Gross / Net Weight	kg	170 / 113.5	
Gross / Net Volume	-1	200 / 170	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Static	
Type of Defrost		Manual	
Refrigerant		R290	
Refrigerant Charge	g	65	
Thermometer		Yes	

Power and Consumption				
Energy Class		С		
Energy Consumption	kWh/24h	4.16		
Annual Energy Cons.	kWh/year	1518		
Max Ambient		30°C at 55% RH		
Input Power	W	212		
Voltage / Frequency	V/Hz	220-240/50		
Voltage / Frequency Noise Level	V/Hz dB(A)	220-240/50		

Dimensions		
Internal Dimension (WxDxH)	mm	1080 x 438 x 401
External Dimension (WxDxH)	mm	1275 x 636 x 1965
Packed Dimension (WxDxH)	mm	1380 x 675 x 1010
40ft Container Load	pcs	48