


BC30 MC

Milk Cooler

Product Features

- Ideal as milk cooler for coffee machines
- Table top cooler with holes, bushings and plugs
- 6 holes 2 in the top, 2 on each side
- Hinged glass door
- Adjustable feet
- · Fan assisted cooling
- LED interior light
- Dispensing tubes not supplied







Lock

Milk Cooler for Coffee Machines

It's an ideal partner for any coffee machines needing a supply of fresh and cooled milk. With 6 holes, closed bushings and plugs on both sides and on the top of the cabinet for maximum flexibility, you get very easy access to the milk, and a hazzle free and convenient producing experience. The cooler is mounted with modern LED light and with adjustable feet.

| Design and Mat | erial | |
|------------------------|-------|---|
| Door No & Type | | 1 hinged self- closing glass door |
| Tempered glass | | Yes |
| Door Reversible | | No |
| Shelves No & Type | | 1 wire shelves black |
| Shelf Color | | Black |
| Shelf Dimensions | | 275 x 205 / 135 mm |
| Max load on Shelves | kg/m² | 196 |
| Feet / Legs | | 4 adjustable feet |
| Exterior Finish | | Black |
| Interior Finish | Coa | ated aluminium, black |
| Interior Light | | LED |
| Lock | | Yes |

| Measures and Content | | | | |
|----------------------|----|-----------|--|--|
| Temperature Range | °C | +2 to +10 | | |
| Climate Class | | 4 | | |
| Gross / Net Weight | kg | 25 / 23 | | |
| Gross / Net Volume | I | 22 / 20 | | |

| Cooling and Functions | | | | |
|-----------------------|---|--------------|--|--|
| Type of Controller | | Mechanical | | |
| Type of Cooling | | Fan assisted | | |
| Type of Defrost | | Automatic | | |
| Refrigerant | | R600a | | |
| Refrigerant Charge | g | 20 | | |
| Thermometer | | No | | |

| Power and Consumption | | | |
|-----------------------|-------------|----------------|--|
| Energy Class | | С | |
| Energy Consumption | kWh/24h | 0.55 | |
| Annual Energy Cons. | kWh/year 20 | | |
| Power | | 1 | |
| Max Ambient | | 30°C at 55% RH | |
| Input Power | W | 60 | |
| Voltage / Frequency | V/Hz | 220-240/50 | |
| Noise Level | dB(A) | 44 | |

| Dimensions | | |
|-------------------------------|-----|-----------------|
| Internal Dimension (WxDxH) | mm | 280 x 271 x 380 |
| External Dimension (WxDxH) | mm | 356 x 430 x 491 |
| Packed Dimension (WxDxH) | mm | 400 x 450 x 520 |
| 40ft Container Load | pcs | 580 |