



## CR 150x180x220

## Coldroom Panels 120 mm

## **Product Features**

- Only panels without cooling unit
- Interlocking connection system
- 120 mm panel insulation
- Many customisation possibilities
- Easy access to products
- · Easy assembly
- Anti-slip floor in SS304 stainless steel
- Shelves available as accessory
- Ramp available as accessory for easy access





Strong handle

Lock system

## Cold room panels with 120 mm insulation

TEFCOLDs cold room panels are quick to assemble with an easy interlocking system. The interchangeable modular panels allow different positioning of the door, so you can build the room to fit your space.

Cold rooms offer an efficient and affordable solution to chilled bulk storage, and are often used in restaurants, delis, cafes, and in the storage rooms of shops and supermarkets.

Our range of cold room panels are equipped with an effective polyurethane insulation. Combine the panels with one of our energy efficient monoblock refrigeration units for high cooling performance and low energy consumption.

In terms of accessories, you have the option of a ramp to provide easy access with lightweight trolleys and bakery racks (the room is not suitable for pallet jacks/pallet trucks). We also offer shelf rack system kits for optimizing storage space. We also offer cold room panels with a wide door (see WD models). The panels are not suitable for outdoor use.

Design and Material		
Door No & Type	1 hinged solid door	
Max Load on Floor kg/m²	2000	
Exterior Finish	White	
Interior Finish	White	
Lock	Yes	

Measures and Content			
Internal Volume	m³	3.85	
Wall Thickness	mm	120	
Insulation Density	kg/m³	42	
Gross / Net Weight	kg	255 / 235	
Gross / Net Volume	1		

Cooling and Functions	
	44142

Power and Consumption				
		44142		
Dimensions				
Internal Dimension (WxDxH)	mm	1260 x 1560 x 1960		
External Dimension (WxDxH)	mm	1500 x 1800 x 2200		
Packed Dimension (WxDxH)	mm	2180 x 1560 x 1150		
40ft Container Load	pcs	14		