

NIC401SCEB

Ice Cream Freezer

Product Features

- Angled display for better presentation
- Curved sliding lids with lock
- Includes full set of baskets
- Ideal for branding
- Digital thermometer
- · Castors with brake
- Climate class 5 for high performance in warm surroundings





Baskets

Lock

Elegant chest freezer with curved sliding glass lids

The NIC-SCEB range is a compact display chest freezer in an elegant design. It has curved corners, rounded edges and curved sliding glass lids.

It is a very stable and solid build, but at the same time on wheels so that it is easy to change location in the shop.

It comes in many sizes, which makes this model perfect for smaller shops and delis with limited space as well as lager shops, gas stations, supermarkets etc.

All sizes are environmental friendly and can be branded for better presentation of the cabinet content.

The SCEB-range is with a lower front than back and curved sliding glass lids. Both features provides a better visual display and presentation of the content. This makes the freezer ideal for display of frozen food including ice cream and lollies. Temperature can be held around -14°C for ice cream or around -21°C for other frozen foods.

All sizes have glass lids with a lock for security. They also have a defrost drain for cleaning out the unit.

Design and Material			
Tempered glass	Yes		
Lid No & Type	2 curved sliding glass lid		
Basket No & Type	5 Wire baskets, white		
Max No. of Baskets p	cs 5		
Castors	4 wheels, 2 with brake		
Exterior Finish	White		
Interior Finish	White painted steel		
Lock	Yes		

Measures and Content				
Temperature Range	°C	-24 to -14		
Climate Class		5		
Gross / Net Weight	kg	87 / 72		
Gross / Net Volume	I	388 / 298		
Cooling and Functions				

Cooling and Fund	tions	
Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	105
Thermometer		Yes

Power and Consumption				
Energy Class		D		
Energy Consumption	kWh/24h	2.27		
Annual Energy Cons.	kWh/year	829		
Input Power	W	179		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	45		

Dimensions		
Internal Dimension (WxDxH)	mm	1180 x 510 x 571
External Dimension (WxDxH)	mm	1320 x 650 x 918
Packed Dimension (WxDxH)	mm	1390 x 765 x 990
40ft Container Load	pcs	50