

## 598 338 315 338

## MD1002X

Stainless Steel Multideck

## **Product Features**

- Premium design
- Stainless steel finish
- Mirror effect end walls
- Adjustable shelves with tilting function
- Shelf stopper for tilting is accessory
- Vertical LED lighting with switch
- · Adjustable feet with rollers at rear
- Night blind / Curtain with soft release
- Fully automatic
- Digital controller and temperature display
- Max shelf weight 50kg per metre



Soft release night blind / curtain



Adjustable shelves with tilting function

## Open front multideck with stainless steel interior and exterior

The TEFCOLD MD-X range of open front multidecks finished in stainless is a great choice for shops, cafes, sandwich shops, butchers and convenience stores. Available in different widths between 685mm and 1885mm there is a size to suit most situations.

The unit is only 680mm deep and is ideal where there is limited floor space but you need to maximise refrigerated display area. With a base shelf and 4 adjustable shelves there is plenty of product storage space. Mirror finish stainless steel interior helps give a sense of space within the cabinet while bright white vertical LED lighting gives excellent illumination of the product (the MD1902X also has a horizontal LED light across the top).

The temperature range can be adjusted to suit your requirement including fresh meat, dairy or soft drinks or beer. Shelves can be angled between 2 and 20 degrees to give extra merchandising options (front shelf stops are required if shelves are angled). The unit comes fitted with rollers to enable the unit to be moved for cleaning, there is also and option for castors. The unit is also available in black.

| Design and Material |                          |  |
|---------------------|--------------------------|--|
| Shelves No & Type   | 4 SS304 shelves, tilting |  |
| Shelf Color         | Stainless steel          |  |
| Feet / Legs         | 2 adjustable feet        |  |
| Castors             | 4 rollers                |  |
| Exterior Finish     | Stainless steel          |  |
| Interior Finish     | Stainless Steel          |  |
| Interior Light      | LED                      |  |

| Measures and Content  |    |           |  |
|-----------------------|----|-----------|--|
| Total Display Area    | m² | 1.1       |  |
| Temperature Range     | °C | -1 to +5  |  |
| Climate Class         |    | 3         |  |
| Gross / Net Weight    | kg | 180 / 162 |  |
| Gross / Net Volume    | T  | 657 / 447 |  |
|                       |    |           |  |
| Cooling and Functions |    |           |  |

| Cooling and Func   | tions |            |
|--------------------|-------|------------|
| Type of Controller |       | Electronic |
| Type of Cooling    |       | Ventilated |
| Type of Defrost    |       | Automatic  |
| Refrigerant        |       | R290       |
| Refrigerant Charge | g     | 105        |

| Power and Consumption |          |                  |  |  |
|-----------------------|----------|------------------|--|--|
| Energy Class          |          | E                |  |  |
| Energy Consumption    | kWh/24h  | 15.7             |  |  |
| Annual Energy Cons.   | kWh/year | 5730             |  |  |
| Power                 |          | 1                |  |  |
| Max Ambient           |          | 25°C at 60% RH   |  |  |
| Input Power           | W        | 820              |  |  |
| Voltage / Frequency   | V/Hz     | 220-240/50       |  |  |
| Noise Level           | dB(A)    | 55               |  |  |
| Dimensions            |          |                  |  |  |
| Internal Dimension    | mm       | 900 x 560 x 1355 |  |  |

(WxDxH)

| Power and Consumption       |     |                   |  |  |  |
|-----------------------------|-----|-------------------|--|--|--|
| External Dimension (WxDxH)  | mm  | 985 x 640 x 1985  |  |  |  |
| Packed Dimension<br>(WxDxH) | mm  | 1070 x 750 x 2140 |  |  |  |
| 40ft Container Load         | pcs | 33                |  |  |  |