

## **BERMUDA RV13**

Scoop Ice Cream Freezer

## **Product Features**

- Perfect temperature distribution
- Heated glass to help prevent condensation
- Suitable for Napoli Pans (not included)
- LED interior light with switch
- Digital controller and temperature display
- Easy access storage compartment
- Rear night curtain to maintain temperature
- Ventilated cooling
- Automatic defrost







Rear night curtain to maintain temperature

## Ventilated 13 scoop ice cream display with understorage

The Bermuda RV13 ice cream scooping cabinet accommodates 13 Napoli pans. Its ventilated cooling system ensures that your gelato or ice cream is maintained at the perfect serving temperature. In addition, the cabinet is equipped with a separate refrigerated under storage, which enables fast restocking of the display without leaving the unit. The Bermuda model has a sleek curved glass feature that is both practical and elegant and the front glass is heated to help prevent condensation. This unit is equipped with castors for easy mobility and an internal LED light that beautifully illuminates your products. With its exceptional blend of quality and affordability, the Bermuda range has become a popular choice among ice cream and gelato vendors.

Design and Material	
SneezeGuard	Yes
Tempered glass	Yes
Castors	4 castors
Exterior Finish	Grey
Interior Finish	White painted steel
Interior Light	LED
Lock	No

Measures and Content				
Serving Capacity		13 Napoli Pans (5 L)		
Storage Capacity (under)		14 Napoli pans (5 L)		
Total Display Area	m²	0.84		
Temperature Range	°C	-20 to -14		
Climate Class		4		
Gross / Net Weight	kg	220 / 200		
Gross / Net Volume	-1	395 / 325		

Cooling and Functions				
Type of Controller		Electronic		
Type of Cooling		Ventilated		
Type of Defrost		Automatic, hot gas		
Refrigerant		R290		
Refrigerant Charge	g	195		
Thermometer		Yes		

Power and Consumption				
Energy Class		D		
Energy Consumption	kWh/24h	22.8		
Annual Energy Cons.	kWh/year	8322		
Max Ambient		30°C at 55% RH		
Input Power	W	1340		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	56		

Dimensions		
Internal Dimension (WxDxH)	mm	1530 x 517 x 232
External Dimension (WxDxH)	mm	1670 x 800 x 1343
Packed Dimension (WxDxH)	mm	1740 x 860 x 1466
40ft Container Load	pcs	13