



## CRNF1212

Freezer room

## **Product Features**

- Plug-In ready after assembly
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Ramp available as accessory for easy access





Strong handle

Shelf as accessory

## Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble.

The cooling unit comes completely pre-mounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door.

The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price.

We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.

Design and Material		Measures and Content			Power and Consumption		
Door No & Type	1 hinged solid door W:580 H:1765	Internal Volume	m <sup>3</sup>	1.81	Energy Consumption	kWh/24	4h 22.49
		Wall Thickness	mm	120	Annual Energy Cons.	kWh/ye	ear 8208
Max Load on Floor kg/m <sup>2</sup>	2000	Insulation Density	kg/m³	42	Input Power	W	1100
Exterior Finish	White	Temperature Range	°C	-20 to -10	Voltage / Frequency	V/Hz	220-240/50
Interior Finish	White	Climate Class		5	Noise Level	dB(A)	60
Interior Light	LED	Gross / Net Weight	kg	310 / 280			
Lock	Yes		Gross / Net Volume I		Dimensions		
200.0	105				Internal Dimension	mm	960 x 960 x 1960
		Cooling and Functions Type of Controller Electronic		(WxDxH)			
				External Dimension (WxDxH)	mm 1200 x 1200 x 2200		
		Type of Cooling		Ventilated			

Measures and Content						
Type of Defrost		Automatic, hot gas				
Refrigerant		R290				
Refrigerant Charge	g	150				
Thermometer		Yes				

Power and Consumption						
Packed Dimension (WxDxH)	mm	2000 x 1350 x 2400				
40ft Container Load	pcs	14				