

CRNF2127

Freezer room

Product Features

- Plug-In ready after assembly
- · Many customisation possibilities
- Easy access to products
- · Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access





Strong handle

Shelf as accessory

Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble.

The cooling unit comes completely pre-mounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door.

The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price.

We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.

| Design and Material | | | |
|-------------------------|--|--|--|
| Door No & Type | 1 hinged solid door W:700 H:1765 | | |
| Max Load on Floor kg/m² | 2000 | | |
| Exterior Finish | White | | |
| Interior Finish | White | | |
| Interior Light | LED | | |
| Lock | Yes | | |

| Measures and Content | | | |
|----------------------|-------|------------|--|
| Internal Volume | m³ | 8.97 | |
| Wall Thickness | mm | 120 | |
| Insulation Density | kg/m³ | 42 | |
| Temperature Range | °C | -20 to -10 | |
| Climate Class | | 5 | |
| Gross / Net Weight | kg | 750 / 720 | |
| Gross / Net Volume | I | | |

| Power and Consumption | | | | |
|-----------------------|----------|----------------|--|--|
| Energy Consumption | kWh/24h | 29.52 | | |
| Annual Energy Cons. | kWh/year | 10775 | | |
| Power | | 1 | | |
| Max Ambient | | 40°C at 40% RH | | |
| Input Power | W | 1394.73 | | |
| Voltage / Frequency | V/Hz | 220-240/50 | | |
| Noise Level | dB(A) | 60 | | |
| | | | | |

Cooling and Functions

Dimensions

| Measures and Cor | ntent | : |
|--------------------|-------|--------------------|
| Type of Controller | | Electronic |
| Type of Cooling | | Ventilated |
| Type of Defrost | | Automatic, hot gas |
| Refrigerant | | R290 |
| Refrigerant Charge | g | 200 |
| Thermometer | | Yes |

| Power and Consumption | | | |
|-------------------------------|-----|--------------------|--|
| Internal Dimension (WxDxH) | mm | 1860 x 2460 x 1960 | |
| External Dimension (WxDxH) | mm | 2100 x 2700 x 2200 | |
| Packed Dimension (WxDxH) | mm | 2150 x 2750 x 2400 | |
| 40ft Container Load | pcs | 6 | |