



CR 180x150x220

Coldroom Panels 120 mm

Product Features

- Only panels without cooling unit
- Interlocking connection system
- 120 mm panel insulation
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- Shelves available as accessory
- Ramp available as accessory for easy access

40ft Container Load

pcs

14





Lock system

Cold room panels with 120 mm insulation

TEFCOLDs cold room panels are quick to assemble with an easy interlocking system. The interchangeable modular panels allow different positioning of the door, so you can build the room to fit your space.

Cold rooms offer an efficient and affordable solution to chilled bulk storage, and are often used in restaurants, delis, cafes, and in the storage rooms of shops and supermarkets.

Our range of cold room panels are equipped with an effective polyurethane insulation. Combine the panels with one of our energy efficient monoblock refrigeration units for high cooling performance and low energy consumption.

In terms of accessories, you have the option of a ramp to provide easy access with lightweight trolleys and bakery racks (the room is not suitable for pallet jacks/pallet trucks). We also offer shelf rack system kits for optimizing storage space. We also offer cold room panels with a wide door (see WD models). The panels are not suitable for outdoor use.

Design and Material		Measures and Content			Power and Consumption		
Door No & Type	1 hinged solid door	Internal Volume	m³	3.85			443
Max Load on Floor kg/m ²	2000	Wall Thickness	mm	120			
Exterior Finish	White	Insulation Density	kg/m³	42	Dimensions		
Interior Finish	White	Gross / Net Weight	kg	460 / 440	Internal Dimension	mm	1560 x 1260 x 19
Lock	Yes	Gross / Net Volume	I		(WxDxH)		
					External Dimension	mm	1800 x 1500 x 22
		Cooling and Functions 44:			(WxDxH)		
				44363	Packed Dimension (WxDxH)	mm	2200 x 1600 x 13