


EXTRA1250FD

Supermarket Multideck Freezer

Product Features

- Can be multiplexed Create uninterrupted continuous line
- Temperature Class 3L1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Solid end walls as standard
- Multiplexing kit as accessory







Electronic thermostat

Full Class Door Multideck Freezer with Multiplexing Option

EXTRA Multideck is a premium full glass door freezer with double glazed hinged glass doors for added energy efficiency savings on running costs. For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Wire shelving with ticket strips and shelf risers are supplied as standard. Installation is simple and quick. No special requirements as refrigerant charge is below 150g. The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

Design and Material			
Door No & Type	2 hinged glass doors		
Tempered glass	Yes		
Door Reversible	No		
Shelves No & Type	8 wire shelves black		
Shelf Color	Black		
Max load on kg/m² Shelves	150		
Feet / Legs	4 adjustable feet		
Castors	Option		
Exterior Finish	Black / Glass		
Interior Finish	Black		
Interior Light	2 x Vertically LED		
Lock	No		

Measures and Content			
Total Display Area	m²	1.53	
Temperature Range	°C	-21 to -18	
Climate Class		3	
Gross / Net Weight	kg	350 / 330	
Gross / Net Volume	1	880 / 850	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic, hot gas	
Refrigerant		R290	
Refrigerant Charge	g	149	
Thermometer		Yes	

Power and Consumption				
Energy Class		D		
Energy Consumption	kWh/24h	15.28		
Annual Energy Cons.	kWh/year	5578		
Input Power	W	1100		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	53		

Dimensions		
Internal Dimension (WxDxH)	mm	1250 x 610 x 1399
External Dimension (WxDxH)	mm	1350 x 930 x 2035
Packed Dimension (WxDxH)	mm	1450 x 975 x 2230
40ft Container Load	pcs	16