

CEV435 BLACK

Black Bottle Cooler

Product Features

- Approx. 40% more energy efficient than CEV425 Black
- Black interior and exterior
- Elegant design
- Great product presentation
- Extra shelf space
- LED light in door frame
- Adjustable shelves
- · Fan assisted cooling
- Reversible door (spare parts needed)
- Lock







Strong handle



LED light inside door frame

Energy-efficient bottle cooler

To offer you a more energy-efficient version of our popular CEV bottle cooler, we have introduced this model with an EU energy class C. The model is otherwise identical to our bestselling CEV model.

This all black bottle cooler is perfect for creating elegant displays of wine, beer, or soft drinks. Use it as a larger upright backbar in bars and restaurants, or make your beverages stand out in retail environments.

The black interior combined with a glass door with LED lighting on the inside of the door frame makes sure that your products are always stylishly displayed. To fully release its marketing potential, have the bottle cooler decorated nicely with customized branding.

The CEV range is available in white or black color options, with a right-hand hinged door or left-hand hinged door, and with or without a canopy.

Design and Mate	rial
Door No & Type	1 hinged glass door
Tempered glass	Yes
Door Reversible	Yes
Shelves No & Type	5 wire shelves black
Shelf Color	Black
Shelf Dimensions	490 x 360 mm
Max load on Shelves	kg/m² 196
Canopy Light	LED
Feet / Legs	2 adjustable feet
Castors	2 rollers
Exterior Finish	Black
Interior Finish	Black
Interior Light	LED inside door frame

Measures and Content			
Temperature Range	°C	+2 to +10	
Climate Class		4	
Gross / Net Weight	kg	80 / 75	
Gross / Net Volume	I	372 / 347	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Fan assisted	
Type of Defrost		Automatic	
Refrigerant		R600a	
Refrigerant Charge	g	70	
Thermometer		Yes	

Power and Consumption			
Energy Class		С	
Energy Consumption	kWh/24h	1.54	
Annual Energy Cons.	kWh/year	563	
Power		1	
Max Ambient		30°C at 55% RH	
Input Power	W	295	
Voltage / Frequency	V/Hz	220-240/50	
Noise Level	dB(A)	45	

Dimensions		
Internal Dimension (WxDxH)	mm	470 x 440 x 1555
External Dimension (WxDxH)	mm	595 x 640 x 1840

Design and Material
Lock Yes

Power and Consumption			
Packed Dimension (WxDxH)	mm	665 x 710 x 2000	
40ft Container Load	pcs	54	