


CRNF1218

Freezer room

Product Features

- Plug-In ready after assembly
- Many customisation possibilities
- Easy access to products
- Freezing unit
- Easy assembly
- 120 mm panel insulation
- Anti-slip floor in SS304 stainless steel
- Alarm kit as accessory
- Shelves available as accessory
- Ramp available as accessory for easy access





Strong handle

Easy, economic and effective storage in freezer room

TEFCOLD freezer rooms are a perfect plug-in solution with quick and easy assemble.

The cooling unit comes completely pre-mounted on a panel and does not require extra expert knowledge. The interchangeable modular panels allow different positioning of both the cooling unit and the panel with the door.

The freezer room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price.

We offer a selection of sizes to fit most situations. The rooms are available as both cooler and freezer options and shelving is available as an option. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the freezer room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms and freezer rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.

Design and Material		Measures and Co	ntent		Power
Door No & Type	1 hinged solid	Internal Volume	m³	2.94	Energy C
	door W:580 H:1765	Wall Thickness	mm	120	Annual E
Max Load on Floor kg/m ²	2000	Insulation Density	kg/m³	42	Input Po
Exterior Finish	White	Temperature Range	°C	-20 to -10	Voltage /
Interior Finish	White	Climate Class		5	Noise Le
Interior Light	LED	Gross / Net Weight	kg	390 / 360	
Lock	Yes	Gross / Net Volume	I		Dimens
LOCK	165				Internal
		Cooling and Functions			(WxDxH)

Power and Consumption				
Energy Consumption	kWh/24h	22.49		
Annual Energy Cons.	kWh/year	8208		
Input Power	W	1100		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	60		

Dimensions		
Internal Dimension (WxDxH)	mm	960 x 1560 x 1960

Measures and Content				
Type of Controller		Electronic		
Type of Cooling		Ventilated		
Type of Defrost		Automatic, hot gas		
Refrigerant		R290		
Refrigerant Charge	g	150		
Thermometer		Yes		

Power and Consumption				
External Dimension (WxDxH)	mm	1200 x 1800 x 2200		
Packed Dimension (WxDxH)	mm	1350 x 2200 x 2400		
40ft Container Load	pcs	12		