



TC57

Ice Maker

Product Features

- Cubed ice approx. 31x35x31mm (18 g)
- Production Capacity: 57 kg/24 h
- Storage Capacity: 28 kg
- · Low energy air-cooled system
- Spray system produces individual clear ice cubes
- · Self-contained ice machine with storage
- Ag+ easy to clean surfaces in the storage bin
- High quality SS304 stainless steel
- 4 Legs and 4 adjustable feet included
- Scoop for ice cubes included
- Fully automatic



Easy to clean condenser filter



Ice cube dimensions

Clear ice maker machine in stainless steel

The TC range of ice makers uses a spray system to produce crystal clear, slow melting ice cubes. This makes the unit ideal for use in cafes, restaurants, pubs, bars, fast-food venues, and other hospitality establishments that require ice for drinks, cocktails, or keeping food such as fresh fish cool.

The exterior of the unit is made from 304 stainless steel; the door at the front of the unit allows quick access to an insulated storage bin, which features Ag+ antibacterial technology to help prevent the formation of bacteria and odors. To ensure that the ice cube maker runs efficiently, the unit has a air filter that is easy to remove and clean.

The TC ice maker uses a low energy air-cooled system, which means it takes in the surrounding air and uses this to cool down the refrigeration system. The capacity of the ice maker is therefore affected by the ambient temperature surrounding it as well as the temperature of the water it takes in.

Design and Material		
Feet / Legs	4 adjustable feet and legs	
Exterior Finish	SS304	

Measures and Content					
Capacity Ice Production	kg/24h	57			
Capacity In Ice Container	kg	28			
Size of Ice Cubes	mm	31 x 35 x 31 (18g)			
Water Consumption	l/24h	84			
Climate Class		5			
Gross / Net Weight	kg	55.6 / 48.15			
Cooling and Functions					

IIL		Power and Consumption		
/24h 57	Energy Consumption	kWh/24h	14.7	
		Annual Energy Cons.	kWh/year	5366
28		Power		1
m	31 x 35 x 31 (18g)	Max Ambient		40°C at 40% RH
 !4h	84	Input Power	W	650
	5	Voltage / Frequency	V/Hz	220-240/50
	55.6 / 48.15	Dimensions		

Dimensions						
External Dimension (WxDxH)	mm	500 x 580 x 800				
Packed Dimension (WxDxH)	mm	555 x 635 x 965				

Electronic

Static

Type of Controller

Type of Cooling

Measures and Content

Refrigerant R290

Refrigerant Charge g 80

Power and Consumption			
40ft Container Load	pcs	144	