



CRPF1221

Cold Room

Product Features

- Plug-In ready after assembly
- Many customisation possibilities
- Easy access to products
- Easy assembly
- Anti-slip floor in SS304 stainless steel
- 80 mm panel insulation
- Shelves available as accessory
- Ramp available as accessory for easy access



Strong handle

Shelf as accessory

otion kWh/24h

W

V/Hz

dB(A)

kWh/year

17.93

6545

220-240/50

830

60

Easy, economic and effective storage in cold rooms

Cold rooms are perfect as plug-in with quick and easy assemble.

The cooling unit comes completely pre-mounted in a panel and does not require extra expert knowledge. The interchangeable modular panels even allow varies positioning of both the panel with the cooling unit and the panel with the door.

The cold room can be used in both restaurants, delis, cafes etc. They are a great way to create optimal and efficient cooling space at a very affordable price. Cold rooms are a perfect and easy accessable way to store foods, dairy products and beverages.

The many different cold room sizes give a good fit in most conditions. Cold rooms are available as both cooler and freezer models. Shelves are optional. A ramp is also available as an option to provide easy access with lightweight trolleys and bakery racks (the cold room is not suitable for pallet jacks/pallet trucks).

Our range of cold rooms have a low energy consumption due to the effective polyurethane insulation in the panels combined with an energy efficient cooling system.

Not suitable for outdoor use.

Design and Material		Measures and Content			Power and Consump
Door No & Type	1 hinged solid	Internal Volume	m³	4.1	Energy Consumption
	door W:580 H:1845	Wall Thickness	mm	80	Annual Energy Cons.
Max Load on Floor kg/m ²	1500	Insulation Density	kg/m³	42	Input Power
Exterior Finish	White	Temperature Range	°C	0 to +8	Voltage / Frequency
Interior Finish	White	Climate Class		5	Noise Level
Interior Light	LED	Gross / Net Weight	kg	290 / 260	
Lock		Gross / Net Volume	I		Dimensions
LOCK	Yes				

TEFCOLD A/S - Industrivej 25 - 8800 Viborg - Denmark - Phone +45 86 60 19 33 - sales@tefcold.com - www.tefcold.com

Measures and Content					
Cooling and Functions					
Type of Controller		Electronic			
Type of Cooling		Ventilated			
Type of Defrost		Automatic, hot gas			
Refrigerant		R290			
Refrigerant Charge	g	130			
Thermometer		Yes			

Power and Consumption						
Internal Dimension (WxDxH)	mm	1040 x 1940 x 2040				
External Dimension (WxDxH)	mm	1200 x 2100 x 2200				
Packed Dimension (WxDxH)	mm	2200 x 1300 x 2400				
40ft Container Load	pcs	14				