


ISABELLA 13LX

Ice Cream Display

Product Features

- Fully automatic
- Sneeze guard in curved glass
- Suitable for Napoli Pans (not included)
- Static cooling
- LED interior light with switch
- Easy access storage compartment
- Digital controller and temperature display
- Rear night curtain to maintain temperature
- Castors







Curved glass for nice presentation

13 scoop static cooled display with understorage

Introducing the Isabella 13 - an expansive ice cream scooping cabinet for 13 pans. The curved glass design creates a stunning display that is sure to captivate your customers and the rear serving shelf helps facilitate quick service. With a built-in refrigerated under storage, restocking the display with fresh ice cream during busy hours is quick and easy, as there's no need to leave the cabinet. Moreover, the cabinet is equipped with castors, making it easy to move around, and an internal LED light that beautifully showcases your ice cream.

| Design and Material | |
|---------------------|-------|
| Exterior Finish | Grey |
| Interior Finish | White |
| Interior Light | LED |

| Measures and Content | | | | |
|--------------------------|----|----------------------|--|--|
| Serving Capacity | | 13 Napoli Pans (5 L) | | |
| Storage Capacity (under) | | 14 Napoli pans (5 L) | | |
| Total Display Area | m² | 0.77 | | |
| Temperature Range | °C | -16 to -14 | | |
| Climate Class | | 4 | | |
| Gross / Net Weight | kg | 223 / 192 | | |
| Gross / Net Volume | 1 | | | |

| Cooling and Functions | | | |
|-----------------------|---|------------|--|
| Type of Controller | | Electronic | |
| Type of Cooling | | Static | |
| Type of Defrost | | Hot Gas | |
| Refrigerant | | R290 | |
| Refrigerant Charge | g | 135 / 45 | |
| Thermometer | | Yes | |
| | | | |

| Power and Consumption | | | | |
|-----------------------|----------|----------------|--|--|
| Energy Class | | С | | |
| Energy Consumption | kWh/24h | 11.84 | | |
| Annual Energy Cons. | kWh/year | 4322 | | |
| Power | | 1 | | |
| Max Ambient | | 30°C at 55% RH | | |
| Input Power | W | 1240 | | |
| Voltage / Frequency | V/Hz | 220-240/50 | | |
| Noise Level | dB(A) | 57 | | |

| Dimensions | | |
|-------------------------------|-----|-------------------|
| Internal Dimension (WxDxH) | mm | |
| External Dimension (WxDxH) | mm | 1647 x 906 x 1372 |
| Packed Dimension (WxDxH) | mm | 1748 x 978 x 1450 |
| 40ft Container Load | pcs | 13 |