DB201H

Backbar Cooler

Product Features

- Approx. 56% more energy efficient than previous DB-range
- Double glazed tempered glass
- Energy saving variable speed compressor
- Ventilated cooling for fast pull-down and even temperature
- Easy access electronic thermostat
- Adjustable shelves
- LED interior light





Protective thermostat cover

Lock

Energy-efficient backbar cooler

This new range of DB backbars is highly energy efficient and uses in average 56% less energy compared to the previous models from the same range. This backbar has ventilated cooling for a short pull-down time to ensure that you can keep up with customer demand for cold beverages. The temperature is easily adjusted on the electronic thermostat.

The backbar cooler has hinged doors with double glazed tempered glass, which gives a nice product presentation. The adjustable wire shelves have a white plastic coating for easy maintenance. The backbar is ideal for busy bar environments, and with its black exterior and stucco aluminium interior it has a contemporary look. A great choice for any bar.

The DB range is also available in a variant with self-closing sliding doors.

Design and Material			
Door No & Type	2 hinged glass doors		
Door Reversible	No		
Tempered glass	Yes		
Shelves No & Type	4 wire shelves white		
Shelf Color	White		
Shelf Dimensions	395x320 mm		
Max load on kg/m² Shelves	196		
Feet / Legs	4 adjustable feet		
Exterior Finish	Black		
Interior Finish	Stucco aluminium		
Interior Light	LED		
Lock	Yes		

Measures and Content			
Total Display Area	m²	0.5	
Temperature Range	°C	+2 to +10	
Climate Class		4	
Gross / Net Weight	kg	69 / 63	
Gross / Net Volume	1	190 / 182	

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R600a	
Refrigerant Charge	g	70	
Thermometer		Yes	

Power and Consumption				
Energy Class		Α		
Energy Consumption	kWh/24h	1.08		
Annual Energy Cons.	kWh/year	394		
Power		1		
Max Ambient		30°C at 55% RH		
Input Power	W	115		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	44		

Dimensions		
Internal Dimension (WxDxH)	mm	810 x 418 x 720
External Dimension (WxDxH)	mm	900 x 520 x 870
Packed Dimension (WxDxH)	mm	985 x 575 x 940
40ft Container Load	pcs	96