

## PC1250B

## Supermarket Multideck Cooler

## **Product Features**

- Frameless glass doors for great product visibility
- Low energy consumption
- Black interior and exterior
- Adjustable shelves with tilting function
- LED light under each shelf
- Ventilated cooling for fast pull-down and even temperature
- Digital controller and temperature display
- Glass end walls as standard
- · Castors and locking feet
- 33 mm ticket strips with shelf risers included





Display with a button LED light under each for each feature

shelf

## Black multideck cooler with frameless glass doors

The PC multideck cooler is all about product visibility and comes with frameless glass doors as well as glass end walls. To further highlight the products, the cooler is equipped with horizontal LED lighting at the top of the cabinet and below each shelf. The 450 mm deep shelves are adjustable and have a tilting function for better product presentation. Front risers are included.

The PC is a spacious cooler with a low energy consumption, and you get a good quality for a competitive price. It is temperature class 3M1, which means it is suitable for display of packed fresh meat, dairy products, fresh fruit and vegetables and is ideal for supermarkets, convenience stores, delis or sandwich shops.

Design and Material				
Door No & Type	2 hinged glass doors			
Tempered glass	Yes			
Shelves No & Type	5 adjustable			
Shelf Color	Black			
Max load on kg/m² Shelves	160			
Feet / Legs	4 adjustable feet			
Castors	4 castors			
Exterior Finish	Black RAL9005			
Interior Finish	Black RAL9005			
Interior Light	LED			

Measures and Content				
Total Display Area	m²	3.14		
Temperature Range	°C	-1 to +5		
Climate Class		3		
Gross / Net Weight	kg	300 / 260		
Gross / Net Volume	1	1292 / 764		

Cooling and Functions			
Type of Controller		Electronic	
Type of Cooling		Ventilated	
Type of Defrost		Automatic	
Refrigerant		R290	
Refrigerant Charge	g	149	
Thermometer		Yes	

Power and Consumption				
Energy Class		В		
Energy Consumption	kWh/24h	5.87		
Annual Energy Cons.	kWh/year	2143		
Input Power	W	550		
Voltage / Frequency	V/Hz	220-240/50		
Noise Level	dB(A)	62		

Dimensions		
Internal Dimension (WxDxH)	mm	1250 x 450 x 1540
External Dimension (WxDxH)	mm	1310 x 740 x 2050
Packed Dimension (WxDxH)	mm	1340 x 770 x 2120
40ft Container Load	pcs	25