


EXTRA1875FD

Supermarket Multideck Freezer

Product Features

- Can be multiplexed Create uninterrupted continuous line
- Temperature Class 3L1
- Heavy duty shelving with strengthening bar
- Adjustable extra deep shelves to maximise capacity
- Ticket strip and acrylic front riser as standard
- Internal vertical LED light
- Base plus 4 shelves
- Solid end walls as standard
- Multiplexing kit as accessory







Electronic thermostat

Full Class Door Multideck Freezer with Multiplexing Option

EXTRA Multideck is a premium full glass door freezer with double glazed hinged glass doors for added energy efficiency savings on running costs.

For greater stock capacity it has 460mm deep shelves to help maximise sales during busy periods and reduce restocking. It has excellent internal illumination with vertical LED lighting in each door and horizontally across the top on the 2500 model. Wire shelving with ticket strips and shelf risers are supplied as standard.

Installation is simple and guick. No special requirements as refrigerant charge is below 150g.

The model allows for multiplexing and increases your possibilities to make the most of the space, you have available. The unit can be ordered without end walls and with a multiplexing kit if required.

| Design and Material | | | | |
|------------------------|-------|-----------------------|--|--|
| Door No & Type | | 3 hinged glass doors | | |
| Tempered glass | | Yes | | |
| Door Reversible | | No | | |
| Shelves No & Type | | 12 wire shelves black | | |
| Shelf Color | | Black | | |
| Max load on Shelves | kg/m² | 150 | | |
| Feet / Legs | | 6 adjustable feet | | |
| Castors | | Option | | |
| Exterior Finish | | Black / Glass | | |
| Interior Finish | | Black | | |
| Interior Light | | 2 x Vertically LED | | |
| Lock | | No | | |

| Measures and Content | | | | |
|----------------------|-------------|--|--|--|
| m² | 2.72 | | | |
| °C | -21 to -18 | | | |
| | 3 | | | |
| kg | 490 / 440 | | | |
| I | 1350 / 1270 | | | |
| | m² °C | | | |

| Cooling and Functions | | | | |
|-----------------------|---|--------------------|--|--|
| Type of Controller | | Electronic | | |
| Type of Cooling | | Ventilated | | |
| Type of Defrost | | Automatic, hot gas | | |
| Refrigerant | | R290 | | |
| Refrigerant Charge | g | 2x144 | | |
| Thermometer | | Yes | | |
| | | | | |

| Power and Consumption | | | | |
|-----------------------|----------|------------|--|--|
| Energy Class | | Е | | |
| Energy Consumption | kWh/24h | 34.76 | | |
| Annual Energy Cons. | kWh/year | 12687 | | |
| Input Power | W | 1860 | | |
| Voltage / Frequency | V/Hz | 220-240/50 | | |
| Noise Level | dB(A) | 53 | | |

| Dimensions | | |
|-------------------------------|-----|-------------------|
| Internal Dimension (WxDxH) | mm | 1875 x 610 x 1399 |
| External Dimension (WxDxH) | mm | 1975 x 930 x 2035 |
| Packed Dimension (WxDxH) | mm | 2075 x 975 x 2230 |
| 40ft Container Load | pcs | 12 |